



# NUBE

DELAY PLUGIN

MANUAL

**ENABLE BUTTON:** Enables/Disables the delay.

**PRESETS BROWSER:** Allows you to select presets.

**PRESETS MENU:** Allows you to load and save presets and banks.

**INPUT LEVEL:** Sets the amount of dry (clean Input) signal (0 to 200%)

**DAMP:** Sets the lowpass decay damping (0%=fast, 100%=slow)

**TIME MODE:** Selects the time of the delay ("Tempo Sync" or "Free" in seconds)

**SPREAD MODE:** Selects the delay mode ("Stereo" or "Ping-Pong")

**STEREO:** Sets the stereo spread (0%=Mono)

**HIGH CUT:** Cuts the high frequencies above the selected value (0 to 22 kHz).

**LOW CUT:** Cuts the low frequencies bellow the selected value (0 to 3 kHz).

**FEEDBACK:** Sets the delay feedback amount (0 to 100%)

**LEVEL:** Sets the amount of wet (processed) signal (0 to 200%)

**FILTER MODE:** Sets the delay filter mode (Low Pass, Band Pass or High Pass)

**FILTER CUTOFF:** Sets the delay filter cutoff frequency.

**FILTER RESONANCE:** Sets the delay filter resonance.

**FILTER LFO RATE:** Sets the filter LFO frequency.

**FILTER LFO DEPTH:** Sets the filter LFO amount.

**PHASER FREQUENCY:** Sets the phaser frequency.

**PHASER LEVEL:** Sets the phaser wet level.

**REVERB DECAY:** Sets the time of the reverb (max. 12 seconds)

**REVERB LEVEL:** Sets the reverb wet level.

***Hint 1:** Double click on a Knob to reset the value.*

***Hint 2:** Press the Ctrl key while moving a Knob to fine adjust the value.*

VST is a trademark of Steinberg Media Technologies GmbH